

SUNLONG SLK6129CNG	
Specification	
SLK6129CNG	
Model	SLK6129CNG
Dimensions and Weights	
Overall length	11,970 mm
Overall width	2,480 mm
Overall height	3,480 mm
Wheelbase	5,980 mm
Vehicle weight (tare)	13,075 kg
Max. G.V.W.	19,500 kg
Passenger seats	33+2
Engine and Performance	
Brand / Power	SDEC 280 PS
Type	CNG, turbocharged, inter-cooler
Pistons and Cylinder Liner	6-cylinder inline
Displacement	8.8 L
Max. output	206 KW / 2,200 rpm
Max. Torque	1,090/1,400 N.m/ rpm
Generator	24 V, 140 Ah
Battery	12 V - 200 Ah x 4
Max. speed	95 km/h
Max. grade ability	25%
Min. turning radius	12 m
Tank Capacity	960 Litre
Emission	Euro III
Power Transmission	
Transmission	Rear-wheel drive
Gear	Manual/ Automatic transmission 6-speed
Final Gear Ratio	5.571
Suspensions and Steering system	
Suspensions F/R	Air Suspension Front 2/ Rear 4
Tyres	Single front dual rear
- Tyre	275/70 R22.5
- Wheel	22.5 x 8.25
Front Brake/Rear Brake	Drum / Drum
ABS	Yes
Eddy current retarder	Yes
Steering System	Right hand steering hydraulic power
Air Conditioning	
Air Conditioning	Songz,31820~34400 kcal/h
Safety System	
Fire extinguisher	Yes (2/4)
Safety belt	Rolling belt
Safety hammer	Yes (6)
Emergency hatches	Yes front & rear with two electric ventilating fans (2)
Emergency door	Yes (1)
Fire extinguisher	Yes (2/4)
Engine compartment auto fire extinguisher	Yes
Disabled stepping	Yes
Disabled parking space	Yes
Tip to get off bell	Yes